

BRYANT

signature series **S**

FC & SA

Bryant-FC Specifications

CODE	ITEM	W	D	AH	BH	SW	SD	SH	WT
BT-C-FC	CHAIR WITH FLAT-CAPPED ARMS	36	34	25	33	21	20	19	95
BT-L-FC	LOVESEAT WITH FLAT-CAPPED ARM	58	34	25	33	21	20	19	120
BT-S-FC	SOFA WITH FLAT-CAPPED ARMS	80	34	25	33	21	20	19	145

W = Width; D = Depth; AH = Arm Height; BH = Back Height; SW = Seat Width; SD = Seat Depth; SH = Seat Height; WT = Weight

Bryant-SA Specifications

CODE	ITEM	W	D	AH	BH	SW	SD	SH	WT
BT-C-SA	CHAIR WITH STRAIGHT ARMS	36	34	25	33	21	20	19	90
BT-L-SA	LOVESEAT WITH STRAIGHT ARMS	58	34	25	33	21	20	19	115
BT-S-SA	SOFA WITH STRAIGHT ARMS	80	34	25	33	21	20	19	140

W = Width; D = Depth; AH = Arm Height; BH = Back Height; SW = Seat Width; SD = Seat Depth; SH = Seat Height; WT = Weight

BACK

The back frame is constructed with 3/4" engineered paneling with the support system constructed of 11-gauge sinuous wire linked together with a 12-gauge tie wire. The back support system is covered with woven material and high-density polymeric foam. The outside back of the frame is covered with woven material and an additional piece of high-density polymeric foam. The back frame is secured to the base frame with patented metal brackets attached to the base frame with metal-to-metal connections.

BASE

The base frame is constructed of 3/4" engineered paneling with support system constructed of 8-gauge sinuous wire linked together with 12-gauge tie wire. Patented metal brackets are attached with bolts into steel receivers creating a metal-to-metal connection. Legs are attached with steel bolts. Legs use plastic non-marking glides.

SEAT

Seat cushions are constructed of high-density, polymeric foam. Seat cushions are secured to the base frame with a nylon security strap.

ARM

Arm frames are constructed of 3/4" engineered paneling. The frames are covered utilizing 80-point chipboard and high-density polymeric foam. The

frames are secured to the base frame with patented metal brackets attached to the base frame with metal-to-metal connections.

UPHOLSTERY

All upholstery offerings conform to California Technical Bulletin 117 fire code standard. All estimated yardage quotes are based on 54" non-matched, solid color material unless otherwise specified. Additional yardage and matching fees may apply.

MOISTURE BARRIER

Foam is wrapped with laminated, polyurethane, moisture-barrier.

ASSEMBLY AND DISASSEMBLY

All components can be disassembled and removed by loosening the thumbscrew and sliding the components out of the interlocking state. Assembly can be completed within minutes. Upholstery fastens with hook and loop, facilitating removal and replacement of covers.

WARRANTY

This product is warranted against defects in materials and workmanship and against structural damage occurred through normal use for 35-years from date of purchase. Foam is also covered under the 35-year period while fabric is generally covered under the fabric company's warranty. Transformations does not warrant any materials beyond its control.

upgrade options

CUSTOM EMBROIDERED LOGOS
TABLET ARM
CAL 133

foot options

Your choice of foot options may change the Arm Height, Back Height, and Seat Height dimensions.



PG40



BT12



*TC23

**Adding Casters to this product is an upgrade.*

v071523

