

HIGHSTREET

signature series **S**

CHAIR/OTTOMAN SLIDE-OUT

Highstreet CSO Specifications

CODE	ITEM	W	D	AH	BH	SW	SD	SH	WT
HS-CSO-FC	FC CHAIR WITH SLIDE-OUT OTTO	30	34	25.5	35.5	22	22	20	95
HS-CSO-RA	RA CHAIR WITH SLIDE-OUT OTTO	37.5	34	25.5	35.5	22	22	20	95
HS-CSO-SA	SA CHAIR WITH SLIDE-OUT OTTO	30	34	25.5	35.5	22	22	20	95
HS-CSO-TA	TA CHAIR WITH SLIDE-OUT OTTO	30	34	25.5	35.5	22	22	20	95
HS-CSO-TX	TX CHAIR WITH SLIDE-OUT OTTO	37.5	34	25.5	35.5	22	22	20	95
HS-CSO-O	SLIDE-OUT OTTOMAN	22	19	-	-	-	-	13	

W = Width; D = Depth; AH = Arm Height; BH = Back Height; SW = Seat Width; SD = Seat Depth; SH = Seat Height; WT = Weight

BACK

The back frame is constructed with 3/4" engineered paneling with the support system constructed of 11-gauge sinuous wire linked together with a 12-gauge tie wire. The back support system is covered with woven material and high-density polymeric foam. The outside back of the frame is covered with woven material and an additional piece of high-density polymeric foam. The back frame is secured to the base frame with patented metal brackets attached to the base frame with metal- to-metal connections.

BASE

The base frame is constructed of both 7/8" and 3/4" engineered paneling with support system constructed of Lexus Webbing. Patented interlocking frame construction is used to attach the seat deck component to the base.

SEAT

Seat cushions are constructed of high-density, polymeric foam. The Seat sits on top of a Lexus Webbing deck. Fabric on the seat cushion attaches to the frame securing it to the unit.

ARM

Arm frames are constructed of 3/4" engineered paneling. The frames are covered utilizing 80-point chipboard and high-density polymeric foam. The frames are secured to the base frame with patented metal brackets attached to the base frame with metal- to-metal connections.

UPHOLSTERY

All upholstery offerings conform to California Technical Bulletin 117 fire code standard. All estimated yardage quotes are based on 54" non-matched, solid color material unless otherwise specified. Additional yardage and matching fees may apply.

MOISTURE BARRIER

Foam is wrapped with laminated, polyurethane, moisture-barrier.

ASSEMBLY AND DISASSEMBLY

All components can be disassembled and removed by loosening the thumbscrew and sliding the components out of the interlocking state. Assembly can be completed within minutes. Upholstery fastens with hook and loop, facilitating removal and replacement of covers.

WARRANTY

This product is warranted against defects in materials and workmanship and against structural damage occurred through normal use for 35-years from date of purchase. Foam is also covered under the 35-year period while fabric is generally covered under the fabric company's warranty. Transformations does not warrant any materials beyond its control.

upgrade options

CUSTOM EMBROIDERED LOGOS
CAL 133

foot options

Your choice of foot options may change the Arm Height, Back Height, and Seat Height dimensions.



*Casters are standard on CSO ottomans, but are not available for CSO chairs.

v071523

