

MAX

signature series 

Max Specifications

CODE	ITEM	W	D	AH	BH	SW	SD	SH	WT
MX-C	CHAIR	40	37	34	34	25	23	20	75

W = Width; D = Depth; AH = Arm Height; BH = Back Height; SW = Seat Width; SD = Seat Depth; SH = Seat Height; WT = Weight

BACK

The back frame is constructed with 7/8" & 3/4" engineered paneling with the support system constructed of 11-gauge sinuous wire linked together with a 12-gauge tie wire. The back support system is covered with woven material and high-density polymeric foam. The outside back of the frame is covered with woven material and an additional piece of high-density polymeric foam. The back frame is secured to the base frame with patented metal brackets attached to the base frame with metal- to-metal connections.

BASE

The base frame is constructed of 7/8" & 3/4" engineered paneling. The support system is constructed of a 9-gauge rigid bar spring unit. Patented metal brackets are attached with bolts into steel receivers creating a metal-to-metal connection. Legs are attached with steel bolts. Legs use plastic non-marking glides.

ARM

The arm frame is constructed with 7/8" & 3/4" engineered paneling with the support system constructed of 11-gauge sinuous wire linked together with a 12-gauge tie wire. The arm support system is covered with woven material and high-density polymeric foam. The outside back of the frame is covered with woven material and an additional piece of high-density polymeric foam. The arm frame is secured to the base frame with patented metal brackets attached to the base frame with metal- to-metal connections.

SEAT

Seat cushion uses high-density, polymeric foam which is wrapped around an innerspring unit. The top is covered with a fiber muslin substrate. The seat is permanently attached to the base frame.

UPHOLSTERY

All upholstery offerings conform to California Technical Bulletin 117 fire code standard. All estimated yardage quotes are based on 54" non-matched, solid color material unless otherwise specified. Additional yardage and matching fees may apply.

MOISTURE BARRIER

Foam is wrapped with laminated, polyurethane, moisture-barrier.

ASSEMBLY AND DISASSEMBLY

No tools are needed. All components can be disassembled and removed by loosening the thumbscrew and sliding the components out of the tamper-proof interlocking stage. Assembly can be completed within minutes without the usage of tools, and all upholstery fastens with hook and loop, facilitating removal and replacement of covers.

WARRANTY

This product is warranted against defects in materials and workmanship and against structural damage occurred through normal use for 35 years from date of purchase. Foam is also covered under the 35-year period while fabric is generally covered under the fabric company's warranty. Transformations does not warrant any materials beyond its control.

CAL 133

CAL 133 is not currently available for Max products.

upgrade options

CUSTOM EMBROIDERED LOGOS

ACCENT THREAD**

foot options



TF07

**Accent Thread is available in several colors: Gold, Green, Turquoise, Blue, Orange, Red, White, Gray, Brown & Black. When ordering the Accent Thread upgrade, please specify your color choice. Colors shown here are for reference only. Contact Customer Service for actual stitched thread samples.



v071523

