



CHASE



v100125

For those who love the chase.

If you like being in the driver's seat, you'll love being in the Chase. With flared arms and a comfortable back, the Chase is designed to bring function to your seating area or residence hall in a sleek and streamlined form. If you're looking to elevate the look of your space, this transitional collection leads the pack.



CHASE

Looking to do a whole room?

Meet the Chase family.



CS-C
CHAIR
32" W X 34" D X 39" H



CS-O
OTTOMAN
28" W X 25" D X 17.5" H



CS-L
LOVESEAT
56" W X 34" D X 39" H



CS-S
SOFA
78" W X 34" D X 39" H

v100125

Custom Embroidered Logos and Brands can be added to any upholstered Transformations Product.



310 RACQUET DR. | FORT WAYNE, IN 46825 | 800.440.9337 | WWW.TRANSFORMATIONSFURNITURE.COM

CHASE

signature series 

Chase Specifications

CODE	ITEM	W	D	AH	BH	SW	SD	SH	WT
CS-C	CHAIR	32	34	27	39	20	21	20.5	75
CS-L	LOVESEAT	56	34	27	39	44	21	20.5	115
CS-S	SOFA	78	34	27	39	66	21	20.5	140
CS-O	OTTOMAN	28	25	-	-	-	-	17.5	30

W = Width; D = Depth; AH = Arm Height; BH = Back Height; SW = Seat Width; SD = Seat Depth; SH = Seat Height; WT = Weight

BACK

The back frame is constructed with 7/8" engineered paneling with the support system constructed of 11-gauge sinuous wire linked together with a 12-gauge tie wire. The back support system is covered with woven material and high-density polymeric foam. The outside back of the frame is covered with woven material and an additional piece of high-density polymeric foam. The back frame is secured to the base frame with patented metal brackets attached to the base frame with metal-to-metal connections.

BASE

The base frame is constructed of 7/8" engineered paneling with support system constructed of 8-gauge sinuous wire linked together with 12-gauge tie wire. Patented metal brackets are attached with bolts into steel receivers creating a metal-to-metal connection. Legs are attached with steel bolts. Legs use plastic non-marking glides.

SEAT

Seat cushions are constructed of high-density, polymeric foam. Seat cushions are secured to the base frame with a nylon security strap.

ARM

Arm frames are constructed of 7/8" engineered paneling. The frames are covered utilizing 80-point chipboard and high-density polymeric foam. The frames are secured to the base frame with patented metal brackets attached to the base frame with metal-to-metal connections.

UPHOLSTERY

All upholstery offerings conform to California Technical Bulletin 117 fire code standard. All estimated yardage quotes are based on 54" non-matched, solid color material unless otherwise specified. Additional yardage and matching fees may apply.

MOISTURE BARRIER

Foam is wrapped with laminated, polyurethane, moisture-barrier.

ASSEMBLY AND DISASSEMBLY

All components can be disassembled and removed by loosening the thumbscrew and sliding the components out of the interlocking state. Assembly can be completed within minutes. Upholstery fastens with hook and loop, facilitating removal and replacement of covers.

WARRANTY

This product is warranted against defects in materials and workmanship and against structural damage occurred through normal use for 35-years from date of purchase. Foam is also covered under the 35-year period while fabric is generally covered under the fabric company's warranty. Transformations does not warrant any materials beyond its control.

upgrade options

CUSTOM EMBROIDERED LOGOS
CAL 133

foot options

Your choice of foot options may change the Arm Height, Back Height, and Seat Height dimensions.



PG40



TF08



*TC23

*TC24

TC24 is a Lockable Caster

**Adding Casters to this product is an upgrade.*

