



RILEY



v100125

Reliable. Stunning. Riley.

Our Riley products are like gold—you can count on them to hold up over time and still look great. This is where comfort and function meet beautiful design. Whether you're creating a formal seating area or a casual hangout, you can't go wrong when you add the Riley collection to your space.



Looking to do a whole room?

Meet the Riley family.



RY-C-TX
CHAIR-TUXEDO ARMS
37.5" W X 34" D X 35" H



RY-O
OTTOMAN
28.5" W X 22" D X 19" H



RY-L-TX
LOVESEAT-TUXEDO ARMS
56.5" W X 34" D X 35" H



RY-S-TX
SOFA-TUXEDO ARMS
79.75" W X 34" D X 35" H

v100125

Custom Embroidered Logos and Brands can be added to any upholstered Transformations Product.



310 RACQUET DR. | FORT WAYNE, IN 46825 | 800.440.9337 | WWW.TRANSFORMATIONSFURNITURE.COM

RILEY

foundations series **F**

Riley Specifications

CODE	ITEM	W	D	AH	BH	SW	SD	SH	WT
RY-C-TX	CHAIR WITH TUXEDO ARMS	37.5	34	26	35	22	21	21.5	75
RY-L-TX	LOVESEAT WITH TUXEDO ARMS	56.5	34	26	35	44	21	21.5	118
RY-S-TX	SOFA WITH TUXEDO ARMS	79.75	34	26	35	66	21	21.5	130
RY-O	OTTOMAN	28.5	22	-	-	-	-	19	24

W = Width; D = Depth; AH = Arm Height; BH = Back Height; SW = Seat Width; SD = Seat Depth; SH = Seat Height; WT = Weight

BACK

The back frame is constructed with 3/4" engineered paneling with the support system constructed of 11-gauge sinuous wire linked together with a 12-gauge tie wire. The back support system is covered with woven material and high-density polymeric foam. The outside back of the frame is covered with woven material and an additional piece of high-density polymeric foam. The back frame is secured to the base frame with patented metal brackets attached to the base frame with metal- to-metal connections.

BASE

The base frame is constructed of 3/4" engineered paneling with support system constructed of 8-gauge sinuous wire linked together with 12-gauge tie wire. Patented metal brackets are attached with bolts into steel receivers creating a metal-to-metal connection. Legs are attached with steel bolts. Legs use plastic non-marking glides.

SEAT

Seat cushions are constructed of high-density, polymeric foam.

ARM

Arm frames are constructed of 3/4" engineered paneling. The frames are covered utilizing 80-point chipboard and high-density polymeric foam. The frames are secured to the base frame with patented metal brackets attached to the base frame with metal- to-metal connections.

UPHOLSTERY

All upholstery offerings conform to California Technical Bulletin 117 fire code standard. All estimated yardage quotes are based on 54" non-matched, solid color material unless otherwise specified. Additional yardage and matching fees may apply.

ASSEMBLY AND DISASSEMBLY

All components can be disassembled and removed by loosening the thumbscrew and sliding the components out of the interlocking state. Assembly can be completed within minutes. Upholstery fastens with hook and loop, facilitating removal and replacement of covers.

WARRANTY

This product is warranted against defects in materials and workmanship, and against structural damage occurred through normal use for 15 years from the date of purchase. Foam is also covered under the 15-year period while fabric is generally covered under the fabric company's warranty. Transformations does not warrant any materials beyond its control.

upgrade options

MOISTURE BARRIER
SECURITY STRAPS
CUSTOM EMBROIDERED LOGOS
CAL 133

foot options

Your choice of foot options may change the Arm Height, Back Height, and Seat Height dimensions.



TC24 is a Lockable Caster

*Adding Casters to this product is an upgrade.

v100125

